

## Technologies of Laser Radiation Focusators

S.R. Abul'khanov

Department of Mechanical Treatment of Materials,  
Samara State Aerospace University (National Research University) Samara, Russia

---

**Abstract:** The study analyzes a wide range of technologies generated by the creation and application of focusators of laser radiation. I give a brief review of methods for solving ill-posed inverse problems of diffraction theory, the methods of monitoring and substrate forming a diffraction micro-relief, optical systems and devices for experimental research of focusators, laser technologies and units on their basis.

**Key words:** Focusators of laser radiation, computational experiment, diffractive optical elements, formation of diffractive microrelief, laser technologies

---

### INTRODUCTION

Functioning of Diffractive Optical Elements (DOE) is based on diffraction of monochromatic light on a microrelief. Due to adjustability of computer-aided design of diffractive microrelief and modern precision equipment capacity for its formation, we have a unique optical tool necessary for required focusing of laser radiation (Golub *et al.*, 1981, 1991a, 1992a).

In the course of years passed since the first publication (Golub *et al.*, 1981) of a revolutionary idea of Prokhorov, Sisakyan, Soifer of a possibility to use diffractive microrelief to achieve a required focusing of laser radiation into a specified area, people developed a wide range of technologies, connected with making and usage of laser radiation focusators.

Possibility to concentrate radiation on a fragment of a surface of a required shape allows to create new technologies and means of their implementation, providing different products with new performance properties. Diffractive optical elements are used in medicine, machine tool building, in optical systems in tooling, food and pharmaceutical industries in lighting engineering in the agricultural sector and also they can be essential for many other types of human activities.

In this research, researchers analyzed the influence of focusators creation on development of diffraction optics, optical instrument making and mechanical-engineering technologies.

### FOCUSATORS DESIGN APPROACH

To design a focusator diffractive microrelief we need to solve an inverse problem of diffraction theory regarding this optical element's phase function. Because of complexity of the inverse problem it is usually solved in the frame of geometrical optics approximation

(Golub *et al.*, 1981, 1991a, b, 1992b; Born and Wolf, 1968; Serafimovich, 2014; Doskolovich *et al.*, 2002, 1995a, b, 1993; Kazanskii, 1989; Kazanskiy *et al.*, 1995; Kazanskiy and Soifer, 1994). Due to ill-posedness of diffraction theory inverse problems in some cases we can see several types of a projected focusator phase function. For example, during focusing into a longitudinal segment (Golub *et al.*, 1981, 1988a; Kazanskii, 1989; Doskolovich *et al.*, 1995a), focusing of a round beam into a rectangular domain (Doskolovich *et al.*, 1993) and so on. Revealing the most effective solution is especially important for basic (the most widespread) problems of focusing. For instance, solving of problems of focusing into a transverse segment (Kazanskiy and Soifer, 1994; Doskolovich *et al.*, 1995b; Soifer *et al.*, 1998) and a ring (Golub *et al.*, 1988a; Soifer, 2013) is basic for focusators directed at letters (Khonina *et al.*, 2011a; Golub *et al.*, 1991c) and solving of problems of focusing into a rectangle is basic for design of focusators for planar domains (Soifer *et al.*, 1995; Doskolovich *et al.*, 1996). It is interesting that solutions obtained for laser radiation focusing appeared to be useful for focusing of surface electromagnetic waves (Bezus *et al.*, 2010, 2011a, b, 2014).

In some cases (for example, complex forms of distribution of intensity or focal region) it is impossible to obtain an analytic expression for the focusator's phase function. In these cases, we apply different iterative methods of solving of inverse problems at approximation of the scalar theory of diffraction (Kazanskii, 1989; Kazanskiy *et al.*, 1994). Developed design methods are combined in corresponding software products (Kazanskiy *et al.*, 1994; Golovashkin *et al.*, 2002; Volotovskii *et al.*, 2001; Doskolovich *et al.*, 1995c; Kazanskiy, 2006, 2012).

To find the best solution, we need to analyze focusators' output parameters (Serafimovich, 2014; Golub *et al.*, 1988a; Doskolovich *et al.*, 2002). Among

characteristics describing processes of creation and functioning of focusators we can mark out three types of parameters (Serafimovich, 2014; Golub *et al.*, 1988a; Doskolovich *et al.*, 2002). The first type includes physical parameters taken as a basis of DOE phase function estimation: focal distance; wave operating length; size of a focusator and a focusing domain and also characteristics describing its shape and a shape of a focused beam; angle of radiation's incidence onto an optical element etc.

The second type includes parameters of discretization and quantization of a focusator's phase function, size and shape of elements of the focusator microrelief spatial resolution. These parameters are connected with choice of a registrar of DOE phase function and specificity of its estimation.

The third type includes focusator's diffractive properties-energy efficiency width of a focal line, root-mean-square deviation of an obtained distribution of intensity in a focal region in comparison with a required one and so on.

For design of focusing DOE the first two types of parameters are internal and diffractive parameters are external, resulting from functioning of a focusator with chosen internal parameters. For research of a focusator it is important to reveal the connection between external and internal parameters of design. Moreover, considering labour required for and multivariance of DOE creation procedure, focusator's characteristics should be studied as early as at the design stage. For such analysis asymptotic methods of research of focusing DOE phase function, information technologies and software tools of computational experiment were developed (Serafimovich, 2014; Golub *et al.*, 1988a; Doskolovich *et al.*, 2002).

#### **ANALYTICAL ASYMPTOTIC METHODS OF RESEARCH**

At the initial stage of creation of a new focusator it is important to carry out an analytical diffractive estimation of the focused radiation taking into account finite size and DOE's concrete physical parameters (Golub *et al.*, 1987; Golub *et al.*, 1992, 1989a; Kazanskiy *et al.*, 2000a; Kazanskiy *et al.*, 1996; Kazanskiy and Kharitonov, 2012; Kazansky, 1990). The analysis of obtained diffractive correlations allows to study limitations of the geometrical optical approach taken as a basis for estimation of the focusator's phase function to reveal initial values of physical parameters which lead to destruction of a required shape of a domain of focusing to find possible mistakes in the diffraction theory inverse problem analytical solution. However, analytical research can be

carried out only for the simplest phase functions, lighting beams and domains of focusing such as ring (Golub *et al.*, 1991, 1987; Soifer, 2013) set of points, longitudinal (Golub *et al.*, 1988a, 1989a; Serafimovich, 2014; Kazanskiy *et al.*, 2000a) and transverse (Kazanskiy *et al.*, 1996; Kazanskiy and Kharitonov, 2012) segments.

In some cases as a result of analytical research one can obtain diffractive corrections to the focusator's phase function. Nevertheless within a framework of an analytical research it is impossible to take account of discretization and quantization of the focusator's phase function which emerge during DOE creation.

#### **COMPUTATIONAL EXPERIMENT**

Methodology and software tools of the computational experiment were developed for further and more comprehensive researches of focusing DOE (Golub *et al.*, 1988a; Kazansky, 1990; Doskolovich *et al.*, 1995d); these methodology and tools allow to account impact of discretization and quantization of a focusator's phase function which emerge during designing and making of DOE.

The same problem arises when focusing problem solution is obtained with the help of different numerical approaches and it is necessary to study obtained solutions thoroughly. The choice of the best solution for concrete internal (first of all physical) parameters of the problem must be done on the basis of computational experiment data (Serafimovich, 2014; Golub *et al.*, 1988a).

The most important line of this research is estimation of energy deposition applied to process material in relation to the focusator's technological role marking, hardening, formation of nanopores and so on.

Presence of a wide range of different methods of focusators diffractive microrelief formation (Popov, 1989; Volkov *et al.*, 2002a, b, 1998; Kazanskiy *et al.*, 2005, 2014; Kazanskii and Kolpakov, 2009; Golub *et al.*, 1995; Pavelyev *et al.*, 2007; Kazanskii *et al.*, 2004, 2007; Abul'khanov *et al.*, 2011, 1993; Bezus *et al.*, 2011a, b) conditions necessity of choosing a concrete way of microrelief creation as early as at the stage of DOE design. A binary microrelief is the simplest to form but blunt "binarying" of the DOE phase function not always allows to preserve required efficiency of an optical element. This was demonstrated by a diffractive research of binary focusators directed at a semiring and a segment with linear distribution of intensity along a focusing segment. The required intensity distribution breakdown was revealed: emerging of a focus ring instead of a semiring, absence of linear growth of intensity along a segment and other negative developments in binary focusators focal

regions (Kazanskiy and Soifer, 1994). To eliminate such negative developments special design methods were suggested (Doskolovich *et al.*, 1995e); these methods allow to increase effectiveness of binary DOE and extend binary microreliefs application field.

The choice of the best solution for concrete internal parameters (in this case parameters of discretization and quantization of the phase function) of a problem is effectively made on the basis of computational experiment results.

### TECHNOLOGIES OF DIFFRACTIVE MICRORELIEF FORMATION

For making of designed focusators many methods and technologies of diffractive microrelief formation were developed (Popov, 1989; Volkov *et al.*, 2002a, b, 1998; Kazanskiy *et al.*, 2005, 2014; Kazanskiy and Kolpakov, 2009; Golub *et al.*, 1995; Pavelyev *et al.*, 2007; Kazanskiy *et al.*, 2004, 2007; Abul'khanov *et al.*, 2011, 1993; Bezus *et al.*, 2011c, d). The choice of a technology depends on the focused radiation wave length, focusator's material and required laser power. Chronologically, the following methods became widely used: hardbaking of dichromated gelatin (Popov, 1989), dark growth in layers of liquid polymerizable compositions (Volkov *et al.*, 2002a), layer-by-layer building-up of photoresist (Volkov *et al.*, 1998), plasmochemical and chemically-assisted ion beam etching, electron-beam lithography (Volkov *et al.*, 2002b; Kazanskiy *et al.*, 2005, 2014; Kazanskiy and Kolpakov, 2009; Golub *et al.*, 1995; Pavelyev *et al.*, 2007; Kazanskiy *et al.*, 2004, 2007), NC cut (Abul'khanov *et al.*, 2011, 1993), plasmon nanolithography (Bezus *et al.*, 2011c, d), etc. The choice of the best diffractive microrelief formation method for concrete internal parameters (in this case parameters of discretization and quantization of the phase function) of a problem is effectively made on the basis of computational experiment results.

For work with high power technological lasers, it is reasonable to process focusators working surface with the help of technological methods connected with metal removing (polishing, smooth finish and lathe work), because in this case a focusator's body is made of a solid workpiece (as a rule of Oxygen-Free copper Cu-OF) (Abul'khanov *et al.*, 2011, 1993) in which coolant ducts are made. Analysis of submicron unevennesses of the focusator's microrelief showed that the best results are achieved with the help of smooth finish and polishing. Technological limits of smooth finish and polishing can be observed in unguaranteed metal removal from the microrelief surface which impairs accuracy of its

processing. In this case, there is no possibility to process zones of undercut of a microrelief, that is such its fragments on which microrelief cylindrical walls are conjugated with surfaces designed to reflection of laser radiation.

Because of specified reasons for focusators surfaces processing it is reasonable to use a cutting edge of natural diamond. Processing of a microrelief with the help of microcutting can provide the accuracy of focusator's work surface making  $>0.1 \mu\text{m}$ . Microrelief should be made with the help of microcutting at the final stage in two stages. At the first stage, we form a microrelief with the accuracy of not  $<1 \mu\text{m}$  with machining equipment using roller bearings or slider bearings and also plain slideways (Abul'khanov *et al.*, 2011, 1993). Then the final processing of the microrelief is performed with depth of cut  $>0.1 \mu\text{m}$ . Finishing treatment of the microrelief may be performed in two cuts. Amount of cuts depends on microrelief height which is defined by the focused laser radiation wave length.

### TECHNOLOGICAL ERRORS ANALYSIS

When impact of discretization and quantization of the phase function on focusator's work can be researched within the framework of the scalar theory of diffraction, impact of minor technological errors of the diffractive microrelief on quality and effectiveness of focusing can be estimated only within the framework of a strict electromagnetic theory, i.e., on the basis of Maxwell's equations solution (Born and Wolf, 1968). For solving of this problem a range of difference schemes (Golovashkin *et al.*, 2004), transparent radiating conditions (Golovashkin and Kazanskiy, 2007), Net Domain Decomposition Method (Golovashkin and Kazanskiy, 2009) and cloud (Kazanskiy and Serafimovich, 2012a, b) and GPGPU-services (Golovashkin and Kasanskiy, 2011) were developed. The developed set of information processing methods allowed to estimate the impact of errors of microrelief formation in the course of laser ablation of polycrystalline diamond films on the functioning of transmitting focusators of infrared band laser radiation (Pavelyev *et al.*, 2006).

### CREATION OF NEW CLASSES OF DOE

Methods which had been developed for focusators turned out to be effective for creation and studying of new classes of diffractive optical elements such as multifocal (Golub *et al.*, 1992c; Soifer *et al.*, 1994) and spectral DOE (Doskolovich *et al.*, 2005a, 2007a) optical antennas (Golub *et al.*, 1989b; Kazanskiy *et al.*, 2000b, c;

Doskolovich *et al.*, 2004) diffractive beam splitters (Kazanskiy and Skidanov, 2012), etc. (Golub *et al.*, 1988b, 1990; Khonina *et al.*, 2011b, c). In particular, mathematical modelling means (before the optical experiment) demonstrated capability of working of the whole DOE's aperture on a composite focal region and also effective functioning of multifocal DOE forming (as distinct from composite DOE) focal lines which are several times thinner. Also, we observed working capacity of spectral DOE forming required distributions of intensity under lighting with monochromatic beams with certain wave lengths from the preset (Doskolovich *et al.*, 2005a, 2007a). Optical antennas appeared to be effective elements of lighting technology devices (Kazanskiy, 2002; Doskolovich *et al.*, 2005a, 2007a; Moiseev *et al.*, 2011; Aslanov *et al.*, 2013).

### **EXPERIMENTAL RESEARCHES**

Nevertheless, analytical methods of researching and careful mathematical modelling are just preparatory research methods. Final decision on possibility of this type of focusing, working capacity of multifocal or spectral DOE, binary beam splitters or optical antennas is taken in view of optical experiment results. Experimental validation of quality passes through all stages of focusators creation. The initial stage is dedicated to cleanness and optical flatness of the base used. For this purpose special methods based on analysis of behaviour of a drop of liquid falling onto the base surface (Borodin *et al.*, 2005, 2009), tribometrical (Kazanskiy *et al.*, 2008a, b), interferential and other approaches (Kazanskiy, 2006, 2012) were developed.

Also, we should note development of methods of microrelief form control (Babin *et al.*, 2009) and different optical schemes and devices for DOE experimental research (Volkov *et al.*, 2001; Golub *et al.*, 1991d; Kazanskiy *et al.*, 2000; Doskolovich *et al.*, 2007c; Karpeev *et al.*, 2007). The most important proof of effectiveness of the developed information and optical technologies is a fair congruence of data of computational and physical experiments for focusator directed at a ring (Doskolovich *et al.*, 2002), diffractive lens (Golub *et al.*, 1991d), different focusators (Kazanskiy *et al.*, 2000d), spectral DOE (Doskolovich *et al.*, 2007c), fiber-optic sensors (Karpeev *et al.*, 2007) and binary beam splitter (Kazanskiy and Skidanov, 2012).

### **TECHNOLOGIES OF FOCUSATORS APPLICATION**

One of the most important ways of practical using of diffractive computer optics is technological application of

focusators. As examples of such ways we can mention laser quenching (Sisakyan *et al.*, 1990; Doskolovich *et al.*, 1993), buildup, marking (Doskolovich *et al.*, 1991), formation of nanopore structures of crystalline (Kazanskiy *et al.*, 2008c) and metal (Kazanskiy *et al.*, 2011; Murzin, 2013) materials and so on. A focusator directed at a ring (Golub *et al.*, 1988a; Soifer, 2013) is used in the installation for growing monocrySTALLINE fibers with the help of a minipedestal method (Bufetova *et al.*, 2006); this installation was developed in the Institute of General Physics of the Russian Academy of Sciences for creation of solid state neodymium lasers. This installation, based on ring laser heating, provides production of high-quality fibers of activated monocrystals with a controlled radial refraction index gradient. A focusator in a set of rings is used for 3D-control of spacer grids of atomic reactor fuel assemblies (Finogenov *et al.*, 2007).

Obtained theoretical and laboratory results found practical use in the real production. Application of focusators allowed to perform thermal quenching of a cutting edge of an edge tool of a complex space form (Soifer *et al.*, 2007). Application of focusators allowed to substantially reduce time spent for thermal quenching and energy consumption too.

Many systems and devices binding edge tool cutting edge corner to a coordinate testify to that this technological problem is still actual. Milling tools used in metalworking have several cutting edges for metal removing. Degree of wear of each cutting edge determines cost effectiveness of milling technological operation and also quality of a surface layer of a piece processed with the help of milling cut. There is no information on means of controlling state of each milling cutter cutting edge right during the processing. Focusators application allows to solve two above mentioned problems at the same time (Abul'khanov *et al.*, 2009), i.e. at the same time to bind a cutting edge corner to a coordinate and to estimate wear degree of each tool's cutting edge. Besides, focusators allow to monitor wear degree of coatings covering the cutting edge.

Acoustic waves focusators give possibility to implement vibration isolation for a specified vpm range and selectively, i.e. for an intended frequency harmonic (Abul'khanov *et al.*, 2012) and that allows to set technological equipment for solving a concrete problem delicately and to a maximum degree of effectiveness. Vibrations applied to tool's zone of contact with a working surface reduce cutting force and that increases energy effectiveness of technological processing, lowers temperature in cutting zone which results in increasing of qualitative parameters of a piece surface layers and also tool hardening. Focusators provide vibrations of required frequency and amplitude on a surface of a specified

shape. In this case, we may achieve vibration frequency not obtainable for other sources of vibrations used in the production and that allows to lower temperature in smooth finish zone. At that burns are avoided, temperature is much lowered in the zone of grinding wheel's contact with a piece's surface, grinding wheel's resistance is improved, we observe no loading of grinding wheel's cutting edge (Evdokimov *et al.*, 2014; Perez *et al.*, 2008; Skuratov *et al.*, 2007).

Giving high-frequency vibrations of small amplitudes to the diamond indenter's zone of contact with a working surface allows to substantially decrease the friction coefficient in the contact zone ( $\ll 0.2$ ) and that practically eliminates heating under piece's surface strain hardening with a diamond sphere. Besides, high-frequency vibrations provide decrease of sizes of hardened metal metallographic structure grains and that in its turn affects piece's performance characteristics favourably.

Focusators allow to give vibrations not only to a surface but also to some space. This property was used for mixing abrasive grains of different fractions up to a high degree of homogeneity (Abul'khanov *et al.*, 1993; Soifer *et al.*, 2011).

Focusators application in the engineering technology allowed to align large and box-type workpieces with machine accessories spindle rotation axis to high precision and also to align optical pieces to high precision too (Abul'khanov *et al.*, 1994).

## CONCLUSION

Developed methods, devices and technologies allowed not only to solve a wide range of problems of creation and research of focusators but also to start designing effective machine vision systems (Volotovskii *et al.*, 2005; Izotov *et al.*, 2011; Kazanskiy and Popov, 2010, 2012) investigating unique properties of diffractive nanophotonics components (Kazanskiy *et al.*, 2010, 2013; Serafimovich *et al.*, 2013; Khonina *et al.*, 2013; Kazanskiy and Serafimovich, 2014; Glushchenko *et al.*, 2011, 2013; Bykov *et al.*, 2010) and creating promising information technologies on this basis (Soifer, 2014) and also to proceed to development of new high-efficiency technological processes.

## ACKNOWLEDGEMENTS

The research was implemented with the support of Ministry of Education and Science of the Russian Federation. These studies were conducted on the equipment of CAM technology common use center.

## REFERENCES

- Abul'khanov, S.R. and L.L. Doskolovich, 1993. The method of processing an aspherical surfaces by cutting and device for its implementation. Patent SU No. 1816532, Bulletin of Inventions No. 19, May 23, 1993.
- Abul'khanov, S.R., A.Y. Dmitriev, N.L. Kazanskiy, V.A. Soifer and S.I. Kharitonov, 2009. Device for contactless measurement of sharpening angles and coordinates of the tool tip for the machines with numerical program control. Patent for Invention RUS 2399461, April 07, 2009.
- Abul'khanov, S.R., E.D. Vasilyev, V.V. Kotlyar and V.A. Soifer, 1994. Laser device for determining the center of rotation details. Patent for Invention SU 2022232, October 30, 1994.
- Abul'khanov, S.R., M.A. Golub, L.L. Doskolovich, V.A. Soifer and S.I. Kharitonov, 1993. Aerosol device. Patent for Invention RUS 1819684, August 07, 1993.
- Abul'khanov, S.R., N.L. Kazanskiy, L.L. Doskolovich and O.Y. Kazakova, 2011. Manufacture of diffractive optical elements by cutting on numerically controlled machine tools. Russian Eng. Res., 31 : 1268-1272.
- Abul'khanov, S.R., N.L. Kazanskiy and V.A. Soifer, 2012. The damper of high frequencies. Patent for Invention RUS 2462630, Russian Bulletin of Inventions No. 27, September 27, 2012.
- Aslanov, E.R., L.L. Doskolovich, M.A. Moiseev, E.A. Bezus and N.L. Kazanskiy, 2013. Design of an optical element forming an axial line segment for efficient LED lighting systems. Opt. Exp., 21: 28651-28656.
- Babin S., L. Doskolovich, Y. Ishibashi, A. Ivanchikov and N. Kazanskiy *et al.*, 2009. SCATT: Software to model scatterometry using the rigorous electromagnetic theory. Proc. SPIE, Vol. 7272. 10.1117/12.816904.
- Bezus, E.A., L.L. Doskolovich and N.L. Kazanskiy, 2011a. Scattering suppression in plasmonic optics using a simple two-layer dielectric structure. Applied Phys. Lett., Vol. 98. 10.1063/1.3597620.
- Bezus, E.A., L.L. Doskolovich, N.L. Kazanskiy and V.A. Soifer, 2011b. Scattering in elements of plasmon optics suppressed by two-layer dielectric structures. Tech. Phys. Lett., 37: 1091-1095.
- Bezus, E.A., L.L. Doskolovich and N.L. Kazanskiy, 2011c. Evanescent-wave interferometric nanoscale photolithography using guided-mode resonant gratings. Microelectronic Eng., 88: 170-174.
- Bezus, E.A., L.L. Doskolovich and N.L. Kazanskiy, 2011d. Interference pattern formation in evanescent electromagnetic waves using waveguide diffraction gratings. Quantum Electronics, 41: 759-764.

- Bezus, E.A., L.L. Doskolovich and N.L. Kazanskiy, 2014. Low-scattering surface plasmon refraction with isotropic materials. *Optics Express*, 22: 13547-13554.
- Bezus, E.A., L.L. Doskolovich, N.L. Kazanskiy, V.A. Soifer and S.I. Kharitonov, 2010. Design of diffractive lenses for focusing surface plasmons. *J. Optics*, Vol. 12. 10.1088/2040-8978/12/1/015001.
- Born, M. and E. Wolf, 1968. *Principles of Optics*. Pergamon Press, Oxford, Pages: 721.
- Borodin, S.A., A.V. Volkov and N.L. Kazanskiy, 2009. Device for analyzing nanoroughness and contamination on a substrate from the dynamic state of a liquid drop deposited on its surface. *J. Opt. Technol.*, 76: 408-412.
- Borodin, S.A., A.V. Volkov and N.L. Kazanskiy, 2005. Automated system for assessing the degree of purity of the substrate dynamic state of drops of a liquid that is applied to its surface. *Comput. Opt.*, 28: 69-75.
- Bufetova, G.A., V.V. Kashin, D.A. Nikolaev, S.Y. Rusanov and V.F. Seregin *et al.*, 2006. Neodymium-doped graded-index single-crystal fibre lasers. *Quantum Electron.*, 36: 616-619.
- Bykov, D.A., L.L. Doskolovich, V.A. Soifer and N.L. Kazanskiy, 2010. Extraordinary magneto-optical effect of a change in the phase of diffraction orders in dielectric diffraction gratings. *J. Exp. Theor. Phys.*, 111: 967-974.
- Doskolovich, L.L., N.L. Kazanskiy, V.A. Soifer and A.Y. Tzaregorodtzev, 1995a. Analysis of quasiperiodic and geometric optical solutions of the problem of focusing into an axial segment. *Optik*, 101: 37-41.
- Doskolovich, L.L., N.L. Kazanskiy and V.A. Soifer, 1995b. Comparative analysis of different focusators focusing into a segment. *Optics Laser Technol.*, 27: 207-213.
- Doskolovich, L.L., M.A. Golub, N.L. Kazanskiy, A.G. Khramov and V.S. Pavelyev *et al.*, 1995c. Software on diffractive optics and computer-generated holograms. *Proc. SPIE*, 2363: 278-284.
- Doskolovich, L.L., N.L. Kazanskiy, S.I. Kharitonov and A.Y. Tzaregorodtzev, 1995d. A method for estimating the DOE's energy efficiency. *Optics Laser Technol.*, 27: 219-221.
- Doskolovich, L.L., N.L. Kazanskiy, P. Perlo, P. Repetto and V.A. Soifer, 1995e. Direct two-dimensional calculation of binary DOEs using a non-binary series expression approach. *Int. J. Optoelectronics*, 10: 243-250.
- Doskolovich, L.L., M.A. Golub, N.L. Kazanskiy, S.I. Kharitonov and V.A. Soifer, 1993. Diffraction investigation of focusators into plane area. *Proc. SPIE*, 1983: 656-657.
- Doskolovich, L.L., N.L. Kazanskiy, P. Repetto and Y.V. Tyavin, 2007a. Design and investigation of colour separation diffraction gratings. *J. Opt.*, 9: 123-127.
- Doskolovich, L.L., N.L. Kazanskiy and S. Bernard, 2007b. Designing a mirror to form a line-shaped directivity diagram. *J. Mod. Opt.*, 54: 589-597.
- Doskolovich, L.L., N.L. Kazanskiy, S.N. Khonina, R.V. Skidanov, N. Heikkila, S. Siitonen and J. Turunen, 2007c. Design and investigation of color separation diffraction gratings. *Applied Opt.*, 46: 2825-2830.
- Doskolovich, L.L., N.L. Kazanskiy and V.A. Soifer, 2002. DOE for Focusing the Laser Light. In: *Methods for Computer Design of Diffractive Optical Elements*, Soifer, V.A. (Ed.). John Wiley and Sons, New York, ISBN: 9780471095330, pp: 347-443.
- Doskolovich, L.L., N.L. Kazanskiy, S.I. Kharitonov and G.V. Uspleniev, 1991. Focusators for laser-branding. *Opt. Lasers Eng.*, 15: 311-322.
- Doskolovich, L.L., N.L. Kazanskiy, S.I. Kharitonov and V.A. Soifer, 1996. A method of designing diffractive optical elements focusing into plane areas. *J. Modern Optics*, 43: 1423-1433.
- Doskolovich, L.L., N.L. Kazanskiy, S.I. Kharitonov, P. Perlo and S. Bernard, 2005b. Designing reflectors to generate a line-shaped directivity diagram. *J. Mod. Opt.*, 52: 1529-1536.
- Doskolovich, L.L., N.L. Kazanskiy, V.A. Soifer, P. Perlo and P. Repetto, 2005. Design of DOEs for wavelength division and focusing. *J. Mod. Opt.*, 52: 917-926.
- Doskolovich, L.L., N.L. Kazanskiy, V.A. Soifer, S.I. Kharitonov and P. Perlo, 2004. A DOE to form a line-shaped directivity diagram. *J. Mod. Opt.*, 51: 1999-2005.
- Evdokimov, D.V., D.G. Fedorov and D.L. Skuratov, 2014. Thermal stress research of processing and formation of residual stress when end milling of a workpiece. *World Applied Sci. J.*, 31: 51-55.
- Finogenov, L.V., Y.A. Lemeshko, P.S. Zavyalov and Y.V. Chugui, 2007. 3D laser inspection of fuel assembly grid spacers for nuclear reactors based on diffractive optical elements. *Measur. Sci. Technol.*, 18: 1779-1785.
- Glushchenko, A.G., E.P. Glushchenko, N.L. Kazanskiy and L.V. Toporkova, 2013. Standing waves in nonreciprocal media. *Comput. Opt.*, 37: 415-418.

- Glushchenko, A.G., G.N. Goncharova, N.L. Kazanskiy and L.V. Toporkova, 2011. Effect of magnetization of magneto-optic structure on the reflection of electromagnetic waves. *Comput. Opt.*, 35: 231-237.
- Golovashkin, D.L. and N.L. Kazanskiy, 2011. Solving diffractive optics problems using graphics processing units. *Optical Memory Neural Networks*, 20: 85-89.
- Golovashkin, D.L. and N.L. Kazanskiy, 2007. Incident wave source conditions for the finite-difference time-domain method: Two-dimensional formulation. *Optoelectronics Instrum. Data Proc.*, 43: 547-555.
- Golovashkin, D.L. and N.L. Kazanskiy, 2009. Mesh domain decomposition in the finite-difference solution of Maxwell's equations. *Optical Memory Neural Networks*, 18: 203-211.
- Golovashkin, D.L., N.L. Kazanskiy, V.A. Soifer, V.S. Pavelyev, V.S. Solovyev, G.V. Usplen'ev and A.V. Volkov, 2002. Technology of DOE Fabrication. In: *Methods for Computer Design of Diffractive Optical Elements*, Soifer, V.A. (Ed.). John Wiley and Sons, New York, pp: 267-345.
- Golovashkin, D.L., N.L. Kazanskiy and V.N. Safina, 2004. Using the finite-difference method for solving the problem of H-wave diffraction with two-dimensional dielectric gratings. *Optical Memory Neural Networks*, 13: 55-62.
- Golub, M.A., I.N. Sisakyan and V.A. Soifer, 1991a. Infrared radiation focusators. *Optics Lasers Eng.*, 15: 297-309.
- Golub, M.A., L.L. Doskolovich, N.L. Kazanskiy, S.I. Kharitonov, N.G. Orlova, I.N. Sisakyan and V.A. Soifer, 1991b. Computational experiment for computer generated optical elements. *Proc. SPIE*, 1500: 194-206.
- Golub, M.A., L.L. Doskolovich, N.L. Kazanskiy, S.I. Kharitonov, I.N. Sisakyan and V.A. Soifer, 1991c. Focusators at letters diffraction design. *Proc. SPIE*, 1500: 211-221.
- Golub, M.A., N.L. Kazanskiy, I.N. Sisakyan, V.A. Soifer, G.V. Usplen'ev, D.M. Yakunenikova and P.S. Spangler, 1991d. Multigradation fresnel lens. *Soviet Phys. Tech. Phys.*, 36: 487-488.
- Golub, M.A., L.L. Doskolovich, N.L. Kazanskiy, I.V. Klimov and V.A. Soifer *et al.*, 1992a. Focusers of near-infrared laser radiation. *Tech. Phys. Lett.*, 18: 39-41.
- Golub, M.A., L.L. Doskolovich, N.L. Kazanskiy, V.A. Soifer and S.I. Kharitonov, 1992b. Diffraction approach to the synthesis of multifunctional phase elements. *Optics Spectroscopy*, 73: 111-113.
- Golub, M.A., L.L. Doskolovich, N.L. Kazanskiy, S.I. Kharitonov and V.A. Soifer, 1992c. Computer generated diffractive multi-focal lens. *J. Mod. Opt.*, 39: 1245-1251.
- Golub, M.A., N.L. Kazanskiy, I.N. Sisakyan, V.A. Soifer and S.I. Kharitonov, 1989a. Diffraction calculation of the field intensity near the focal line of a focuser. *Optics Spectroscopy*, 67: 814-815.
- Golub, M.A., N.L. Kazanskiy, A.M. Prokhorov, I.N. Sisakyan and V.A. Soifer, 1989b. Synthesis of optical antennae. *Comput. Opt.*, 1: 25-28.
- Golub, M.A., N.L. Kazanskiy, I.N. Sisakyan and V.A. Soifer 1988a. Computational experiment with plane optical elements. *Optoelectron. Instrum. Data Process.*, 1: 78-89.
- Golub, M.A., S.V. Karpeev, N.L. Kazanskiy, A.V. Iirziv, I.N. Sisakyan, V.A. Soifer and G.V. Uvariv, 1988b. Spatial phase filters matched to transverse modes. *Soviet J. Quantum Electron.*, 18: 392-393.
- Golub, M.A., N.L. Kazanskiy, I.N. Sisakyan, V.A. Soifer and S.I. Kharitonov, 1987. Diffraction calculation for an optical element which focuses into a ring. *Optoelectron. Instrum. Data Process.*, 6: 7-14.
- Golub, M.A., N.L. Kazanskiy, I.N. Sisakyan and V.A. Soifer, 1990. Wave fronts forming by computer generated optical elements. *Proc. SPIE*, 1183: 727-750.
- Golub, M.A., O.E. Rybakov, G.V. Usplen'ev, A.V. Volkov and S.G. Volotovskiy, 1995. The technology of fabricating focusators of infrared laser radiation. *Optics Laser Technol.*, 27: 215-218.
- Golub, M.A., S.V. Karpeev, A.M. Prokhorov, I.N. Sisakyan and V.A. Soifer, 1981. Focusing light into a specified volume by computer-synthesized holograms. *Sov. Tech. Phys. Lett.*, 7: 264-265.
- Izotov, P.Y., N.L. Kazanskiy, D.L. Golovashkin and S.V. Sukhanov, 2011. CUDA-enabled implementation of a neural network algorithm for handwritten digit recognition. *Opt. Memory Neural Networks*, 20: 98-106.
- Karpeev, S.V., V.S. Pavelyev, S.N. Khonina, N.L. Kazanskiy, A.V. Gavrilov and V.A. Erolov, 2007. Fibre sensors based on transverse mode selection. *J. Modern Opt.*, 54: 833-844.
- Kazanskiy, N.L. and V.A. Kolpakov, 2009. Effect of bulk modification of polymers in a directional low-temperature plasma flow. *Tech. Phys.*, 54: 1284-1289.
- Kazanskiy, N.L., 1989. Correction of focuser phase function by computer-experimental methods. *Comput. Optics*, 1: 69-73.
- Kazanskiy, N.L., A.I. Kolpakov, V.A. Kolpakov and V.D. Parandin, 2007. Temperature measurement of a surface exposed to a low-temperature plasma flux. *Tech. Phys.*, 52: 1552-1556.
- Kazanskiy, N.L., V.A. Kolpakov and A.I. Kolpakov, 2004. Anisotropic etching of SiO<sub>2</sub> in high-voltage gas-discharge plasmas. *Russian Microelectro.*, 33: 169-182.

- Kazanskiy, N. and R. Skidanov, 2012. Binary beam splitter. *Applied Opt.*, 51: 2672-2677.
- Kazanskiy, N.L. and P.G. Serafimovich, 2012b. Cloud computing for nanophotonic simulations. *Proceedings of the 4th International Workshop on Optical Supercomputing*, July 19-21, 2012, Bertinoro, Italy, pp: 54-67.
- Kazanskiy, N.L. and P.G. Serafimovich, 2012a. Cloud computing for rigorous coupled-wave analysis. *Adv. Optical Technol.*, Vol. 2012. 10.1155/2012/398341.
- Kazanskiy, N.L. and P.G. Serafimovich, 2014. Coupled-resonator optical waveguides for temporal integration of optical signals. *Opt. Exp.*, 22: 14004-14013.
- Kazanskiy, N.L. and S.B. Popov, 2010. Machine vision system for singularity detection in monitoring the long process. *Opt. Memory Neural Networks*, 19: 23-30.
- Kazanskiy, N.L. and S.B. Popov, 2012. Distributed storage and parallel processing for large-size optical images. *Proc. SPIE*, Vol. 8410. 10.1117/12.928441.
- Kazanskiy, N.L. and S.I. Kharitonov, 2012. Transmission of the space-limited broadband symmetrical radial pulses focused through a thin film. *Comput. Optics*, 36: 4-13.
- Kazanskiy, N.L. and V.A. Soifer, 1994. Diffraction investigation of geometric-optical focusators into segment. *Optik*, 96: 158-162.
- Kazanskiy, N.L., 2002. DOE-Based Lighting Devices. In: *Methods for Computer Design of Diffractive Optical Elements*, Soifer, V.A. (Ed.). John Wiley and Sons, New York, USA., pp: 651-671.
- Kazanskiy, N.L., 2006. Research complex for solving problems of computer optics. *Comput. Optics*, 29: 58-77, (In Russian).
- Kazanskiy, N.L., 2012. Research and education center of diffractive optics. *Proc. SPIE*, Vol. 8410. 10.1117/12.923233.
- Kazanskiy, N.L., G.A. Podlipnov, A.A. Rakhaev and M.L. Sosnin, 2000a. Computation of the electromagnetic field in longitudinally regular structure. *Optical Memory Neural Networks*, 9: 23-29.
- Kazanskiy, N.L., S.I. Kharitonov and V.A. Soifer, 2000b. Simulation of DOE-aided focusing devices. *Opt. Memory Neural Networks*, 9: 191-200.
- Kazanskiy, N.L., S.I. Kharitonov, V.A. Soifer and A.V. Volkov, 2000c. Investigation of lighting devices based on diffractive optical elements. *Opt. Memory Neural Networks*, 9: 301-312.
- Kazanskiy, N.L., G.V. Uspleniev and A.V. Volkov, 2000d. Fabricating and testing diffractive optical elements focusing into a ring and into a twin-spot. *Proc. SPIE*, 10.1117/12.407678.
- Kazanskiy, N.L., P.G. Serafimovich and S.N. Khonina, 2010. Harnessing the guided-mode resonance to design nanooptical transmission spectral filters. *Opt. Memory Neural Networks*, 19: 318-324.
- Kazanskiy, N.L., P.G. Serafimovich and S.N. Khonina, 2013. Use of photonic crystal cavities for temporal differentiation of optical signals. *Opt. Lett.*, 38: 1149-1151.
- Kazanskiy, N.L., S.I. Kharitonov and V.A. Soifer, 1995. Calculation of the field formed by a focusator illuminated by Gaussian-Hermite beams. *Proc. SPIE*, 2363: 285-289.
- Kazanskiy, N.L., S.I. Kharitonov and V.A. Soifer, 1996. Application of a pseudogeometrical optical approach for calculation of the field formed by a focusator. *Optics Laser Technol.*, 28: 297-300.
- Kazanskiy, N.L., V.A. Kolpakov, A.I. Kolpakov, S.V. Krichevsky, N.A. Ivliev and M.V. Desjatov, 2008a. Parameter optimization of a tribometric device for rapid assessment of substrate surface cleanliness. *Opt. Memory Neural Networks*, 17: 167-172.
- Kazanskiy, N.L., S.V. Karpeev, V.A. Kolpakov, S.V. Krichevsky and N.A. Ivliev, 2008b. Interaction of dielectric substrates in the course of tribometric assessment of the surface cleanliness. *Opt. Memory Neural Networks*, 17: 37-42.
- Kazanskiy, N.L., S.P. Murzin, A.V. Mejenin and Y.L. Osetrov, 2008c. The formation of laser radiation to create nanoscale porous structures materials. *Comput. Opt.*, 32: 246-248, (In Russian).
- Kazanskiy, N.L., S.P. Murzin, Y.L. Osetrov and V.I. Tregub, 2011. Synthesis of nanoporous structures in metallic materials under laser action. *Opt. Lasers Eng.*, 49: 1264-1267.
- Kazanskiy, N.L., V.A. Kolpakov and A.I. Kolpakov, 2005. Studies on a mechanism of catalytic mask generation in irradiation of an al-si structure with high-voltage gas-discharge particles. *Optical Memory Neural Networks (Inform. Optics)*, 14: 151-160.
- Kazanskiy, N.L., V.A. Kolpakov and V.V. Podlipnov, 2014. Gas discharge devices generating the directed fluxes of off-electrode plasma. *Vacuum*, 101: 291-297.
- Kazanskiy, N.L., V.V. Kotlyar and V.A. Soifer, 1994. Computer-aided design of diffractive optical elements. *Optical Eng.*, 33: 3156-3166.
- Kazanskiy, N.L., 1990. Numerical experiment with a Fresnel lens. *Comput. Optics*, 2: 17-21.
- Khonina, S.N., N.L. Kazanskiy and S.G. Volotovskiy, 2011a. Influence of vortex transmission phase function on intensity distribution in the focal area of high-aperture focusing system. *Optical Memory Neural Networks*, 20: 23-42.



- Khonina, S.N., N.L. Kazanskii, A.V. Ustinov and S.G. Volotovskii, 2011b. The lensacon: Nonparaxial effects. *J. Opt. Technol.*, 78: 724-729.
- Khonina, S.N., N.L. Kazanskiy and S.G. Volotovskiy, 2011c. Vortex phase transmission function as a factor to reduce the focal spot of high-aperture focusing system. *J. Mod. Opt.*, 58: 748-760.
- Khonina, S.N., S.G. Volotovskiy, S.I. Kharitonov and N.L. Kazanskiy, 2013. Calculating the energy spectrum of complex low-dimensional heterostructures in the electric field. *Scient. World J.*, 10.1155/2013/807462.
- Moiseev, M.A., L.L. Doskolovich and N.L. Kazanskiy, 2011. Design of high-efficient freeform LED lens for illumination of elongated rectangular regions. *Opt. Exp.*, 19: A225-A233.
- Murzin, S.P., 2013. Exposure to laser radiation for creation of metal materials nanoporous structures. *Opt. Laser Technol.*, 48: 509-512.
- Pavelyev, V.S., S.A. Borodin, N.L. Kazanskiy, G.F. Kostyuk and A.V. Volkov, 2007. Formation of diffractive microrelief on diamond film surface. *Optics Laser Technol.*, 39: 1234-1238.
- Pavelyev, V.S., V.A. Soifer, N.L. Kazanskiy, D.L. Golovashkin and A.V. Volkov *et al.*, 2006. Synthesis and investigation of diamond diffractive optical elements. *Proc. SPIE*, Vol. 6200. 10.1117/12.682129.
- Perez, J., S. Hoyas, D.L. Skuratov, Y.L. Ratis, I.A. Selezneva, P.F. de Cordoba and J.F. Urchueguia, 2008. Heat transfer analysis of intermittent grinding processes. *Int. J. Heat Mass Transfer*, 51: 4132-4138.
- Popov, V.V., 1989. Materials and methods for flat optical elements. *Comput. Optics*, 1: 125-128.
- Serafimovich, P.G., 2014. Diffraction analysis of focusing optical elements. *Proc. SPIE*, Vol. 9156. 10.1117/12.2054492.
- Serafimovich, P.G., N.L. Kazanskiy and S.N. Khonina, 2013. Two-component cavity based on a regular photonic crystal nanobeam. *Applied Opt.*, 52: 5830-5834.
- Sisakyan, I.N., V.P. Shorin, V.A. Soifer, V.I. Mordasov and V.V. Popov, 1990. Technological capabilities of focusators in laser-induced material processing. *Comput. Opt.*, 2: 85-87.
- Skuratov, D.L., Y.L. Ratis, I.A. Selezneva, J. Perez, P.F. de Cordoba and J.F. Urchueguia, 2007. Mathematical modelling and analytical solution for workpiece temperature in grinding. *Applied Math. Modell.*, 31: 1039-1047.
- Soifer, V.A., 2013. *Computer Design of Diffractive Optics*. Woodhead Publishing Ltd., USA., ISBN: 978-1-84569-635-1, Pages: 896.
- Soifer, V.A., 2014. Diffractive nanophotonics and advanced information technologies. *Herald Russian Acad. Sci.*, 84: 9-20.
- Soifer, V.A., L.L. Doskolovich and N.L. Kazanskiy, 1994. Multifocal diffractive elements. *Opt. Eng.*, 33: 3610-3615.
- Soifer, V.A., L.L. Doskolovich, N.L. Kazanskiy and V.S. Pavelyev, 1995. Hybrid method for calculating diffractive optical elements (DOEs) focusing into radial focal domain. *Proc. SPIE*, 2426: 358-365.
- Soifer, V.A., N.L. Kazanskiy and S.I. Kharitonov, 1998. Synthesis of a binary DOE focusing into an arbitrary curve, using the electromagnetic approximation. *Optics Lasers Eng.*, 29: 237-247.
- Soifer, V.A., N.L. Kazanskiy, S.R. Abul'khanov, L.L. Doskolovich and S.I. Kharitonov, 2007. Device for thermal hardening of the cutting edge of the cutter. Patent for Invention RUS 2341 568, January 09, 2007.
- Soifer, V.A., N.L. Kazanskiy, Y.S. Strelkov, A.Y. Dmitriev, L.L. Doskolovich and S.I. Kharitonov, 2011. Vibrating mixer. Patent for Invention RUS 2422195, June 27, 2011.
- Volkov, A.V., N.L. Kazanskii and G.V. Usplenev, 2001. Automation of the physical experiment in computer optics. *Pattern Recognit. Image Anal.*, 11: 469-470.
- Volkov, A.V., N.L. Kazanskiy, O.J. Moiseyev and V.A. Soifer, 1998. A method for the diffractive microrelief formation using the layered photoresist growth. *Optics Lasers Eng.*, 29: 281-288.
- Volkov, A.V., N.L. Kazansky and V.S. Solovjev, 2002a. Checking the refractive index change in liquid photopolymerizable compositions. *Proc. SPIE*, 4680: 214-219.
- Volkov, A.V., N.L. Kazansky, G.F. Kostyuk and V.S. Pavelyev, 2002b. Dry etching of polycrystalline diamond films. *Optical Memory Neural Networks (Inform. Optics)*, 11: 135-137.
- Volotovskii, S.G., N.L. Kazanskii, P.G. Serafimovich and S.N. Khonina, 2001. Modern information technologies in computer optics. *Pattern Recogn. Image Anal.*, 11: 471-473.
- Volotovskii, S.G., N.L. Kazanskii, S.B. Popov and R.V. Khmelev, 2005. Machine vision system for registration of oil tank wagons. *Pattern Recognit. Image Anal.*, 15: 461-463.